

HEXA PHENOLIC LAMINATED PANELS



**One Side 185gsm Matt Black
Smooth Phenolic Film**

**One Side 185gsm Matt Black
Hexagonal Pattern Phenolic Film**



1.22m x 2.44m High Quality Birch Plywood Panels Overlaid with Matt Black Hexagonal Pattern Phenolic Film

Filmfaced plywood is a flat sheet, consisting of five or more layers of birch veneer glued together and overlaid with a phenolic film.

Multilayer and mutually perpendicular direction of the fibers in the adjacent layers provide plywood with strength in both directions, shape stability, which is an advantage compared to other wooden materials.

Filmfaced plywood is durable but light material, which can be easily processed, has high wear resistance and is water proof. Can be use outside and is resistant to chemicals and ultraviolet.

Perfect for applications where high wear resistance are required.

Plywood is glued with phenol-formaldehyde resin and meets the demands of the standards EN 13986 and EN 314-3. Class of formaldehyde emission E1 and CARB phase 2 standards. Physical and mechanical properties meet the requirements of EN 13986.

Part No.	Nominal Thickness	Side One	Side Two	Thickness	Tolerance	Nominal Weight
M847108	6.5mm	Hexa Black	Smooth Black	6.5mm	+0/-0.5mm	13.5kg
M847111	9.5mm			9.5mm	+0/-0.5mm	19kg
M847113	12mm			12mm	+0/-0.5mm	24kg
M847211	9.5mm	Hexa Blue	Smooth Black	9.5mm	+0/-0.5mm	19kg
M847213	12mm			12mm	+0/-0.5mm	24kg